

API 7K

应用：超高压液压流体输送且压强变化大或者易弯曲的工程机械，煤矿和性能要求的工业应用

Application: Very high pressure applications subject to surge or flexing such as construction equipment, mining and the high-performance industrial market.



内 胶：合成橡胶

增 强 层：六层交互缠绕高强度钢丝

外 胶：黑色合成橡胶

应用温度：-40 °F 至 +250 °F (-40°C 至 +121°C)

应用标准：GB/T 10544 R13, EN 856 R13, SAE J517 R13, API 7K

Inner Tube :Synthetic rubber

Reinforcement:six alternating layers of spiralled high tensile steel wire

Cover: Black synthetic rubber

Temperature Range:-40 °F to +250 °F (-40°C to 121°C)

Applicable Standards: GB/T 10544 R13, EN 856 R13, SAE J517 R13, API 7K

标识 Branding:



产品编号 Product Number	Hose ID 胶管内径		W.D. 外层钢丝直径		C.O.D 外胶直径	Max W.P. 最大工作压力	Test Pressure 测试压力	Min B.P. 最小爆破	Min B.R. 最小弯曲半径	Weight 参考重量		
	mm	in	Min 最小 mm	Max 最大 mm	Max 最大 mm	Mpa	Mpa	Mpa	mm	kg/m		
API 7k-32-51	51	2	50.4	52.0	66.9	69.3	72.7	69.0	103.4	153.3	700	7.33