

SR1SN

应用: 中等压力的液压应用, 包括移动, 机床和农业的应用, 使用油基或水基液压油。

Application: Medium pressure hydraulic application including mobile, machine tooling and agricultural application, using oil based or water based hydraulic fluids.



内 胶: 合成橡胶

增 强 层: 一层高强度编织钢丝

外 胶: 合成橡胶

应用温度: -40 °F 至 +212 °F (-40°C 至 +100°C)

应用标准: EN853 1SN, SAE J517 R1S, GB3683.1 1SN, ISO 1436 1SN MT 98, 煤安 MA, 美国 MSHA 和 SAE J1942/USCG 认证

安全系数: 4:1

Inner Tube: Synthetic Rubber

Reinforcement: one braid of high-tensile steel wire


Cover: Synthetic Rubber

Temperature Range: -40 °F to +212 °F (-40°C to +100°C)

Applicable Standards: EN853 1SN, SAE J517 R1S, GB3683.1 1SN, ISO 1436 1SN, MT 98, Certificate of MA, US MSHA and SAE J1942/U.S. Coast Guard

Safe factor: 4:1

标识 Branding:



| 产品编号 Product Number | Hose ID 胶管内径 | | W.D. 外层钢丝直径 | | C.O.D 外径直径 | | Max W.P. 最大工作压力 | | Min B.R. 最小弯曲半径 | | Weight 参考重量 |
|------------------------|-----------------|-------|-----------------|-----------------|-----------------|-----------------|--------------------|------|--------------------|-----|----------------|
| | mm | in | Min 最小 mm | Max 最大 mm | Min 最小 mm | Max 最大 mm | Max 最大 mm | Mpa | psi | mm | kg/m |
| SR1SN-04-06 | 6.3 | 1/4 | 6.2 | 7 | 10.6 | 11.6 | 14.1 | 22.5 | 3260 | 100 | 0.23 |
| SR1SN-05-08 | 8 | 5/16 | 7.7 | 8.5 | 12.1 | 13.3 | 15.7 | 21.5 | 3120 | 115 | 0.27 |
| SR1SN-06-10 | 10 | 3/8 | 9.8 | 10.3 | 14.5 | 15.7 | 18.1 | 18 | 2615 | 130 | 0.34 |
| SR1SN-08-13 | 12.5 | 1/2 | 12.3 | 13.5 | 17.5 | 19.1 | 21.4 | 16 | 2320 | 180 | 0.43 |
| SR1SN-10-16 | 16 | 5/8 | 15.5 | 16.7 | 20.6 | 22.2 | 24.5 | 13 | 1890 | 200 | 0.51 |
| SR1SN-12-19 | 19 | 3/4 | 18.6 | 19.8 | 24.6 | 26.2 | 28.5 | 10.5 | 1530 | 240 | 0.66 |
| SR1SN-16-25 | 25 | 1 | 25 | 26.4 | 32.5 | 34.1 | 36.6 | 8.7 | 1280 | 300 | 1.00 |
| SR1SN-20-32 | 31.5 | 1 1/4 | 31.4 | 33 | 39.3 | 41.7 | 44.8 | 6.3 | 920 | 420 | 1.35 |
| SR1SN-24-38 | 38 | 1 1/2 | 37.7 | 39.3 | 45.6 | 48 | 52.1 | 5 | 730 | 500 | 1.56 |
| SR1SN-32-51 | 51 | 2 | 50.4 | 52 | 58.7 | 61.7 | 65.5 | 4 | 580 | 630 | 2.20 |
| SR1SN-40-64 | 64 | 2 1/2 | 63.1 | 65.1 | 71.5 | 73.5 | 77.4 | 5 | 720 | 760 | 2.55 |
| SR1SN-48-76 | 76 | 3 | 75.8 | 78.8 | | | 90 | 5 | 720 | 900 | 2.87 |